

Product Specification

KOMODO® Vigilant® Cut 1



Product Information

Trade name: KOMODO® Vigilant® Cut 1

Intended use: To protect the user from Cut 1 mechanical risks (tear, abrasion, cut & puncture) and light chemical risks during mechanical tasks, whilst maintaining comfort and dexterity. Precision thumbs and forefingers for accurate, easy use of touch screens.

Materials: Technical yarn, glass fibre, nylon and spandex. Nitrile dipped palm, fingers and fingertips.

Cut rating: 1 - 1,2 factor.

Cuff finishing: Double stitched elastic cuff.

Colour: Highly Vigilant® green with black nitrile dipped palm and finger. Black lines on cuff.

UOM: 1 pair.

Sizes: Small, Medium, Large, XL, XXL.



KOMODO® Verda Tech Product Specification

Dimensions	Size	Palm width	Length (mm)
	Small	78 ± 3mm	240 (minimum)
	Medium	84 ± 3mm	240 (minimum)
	Large	94 ± 3mm	240 (minimum)
	X Large	105 ± 3mm	240 (minimum)
	XX Large	113 ± 3mm	240 (minimum)
Thickness	Palm	Finger	Touch screen fingertips
	0.85mm	0.85mm	0.80mm

Packaging Configuration & Labelling:

Packing: 120 pairs per case (12 pairs per inner bag)

Labelling: The inner tags and outer cartons have the following information: product description, brand, size and net quantity of gloves, country of origin, name and address of distributor and EN388 mechanical protection symbol.

Barcodes: GS1 format.

Hangtag



EN388 - Mechanical Risks

Pictogram	Abrasion	Cut	Tear	Puncture
EN388 2121	2 <i>This 1-4 digit represents how many cycles of a coarse surface the glove can handle until failure.</i> 1 = 100 2 = 500 3 = 2000 4 = 8000	1 1 = 1,2 factor. 2 = 2,5 factor. 3 = 5 factor. 4 = 10 factor. 5 = 20 factor.	2 <i>The higher this 1-4 digit the more torque (Nm) a glove can take in a tearing motion.</i> 1 = 10 Nm 2 = 25 Nm 3 = 50 Nm 4 = 75 Nm	1 1 = 20 Nm until break. 2 = 60 Nm until break. 3 = 100 Nm until break. 4 = 150 Nm until break.

For more information: customer.service@theglovecompany.com