

# Product Specification

## KOMODO® Cut 5



### Product Information

Trade name: KOMODO® Cut 5

Intended use: To protect the user from mechanical (tear, abrasion, cut & puncture) during mechanical tasks, whilst maintaining comfort and dexterity.

Materials: Double dipped sandy nitrile.

Cut rating: 5 (20 factor)

Cuff finishing: Double stitched elastic cuff.

Colour: Red with white threads on cuff, black palm and fingers.

UOM: 1 pair.

Sizes: Small, Medium, Large, XL, XXL.



Product Specification			
<b>Dimensions</b> Millimetres (Inches)	<b>Size</b>	<b>Palm width</b>	<b>Length (mm)</b>
	Small	78 ± 3mm (3.07" ± 0.1")	240 (minimum) (9.44")
	Medium	84 ± 3mm (3.30" ± 0.1")	240 (minimum) (9.44")
	Large	94 ± 3mm (3.70" ± 0.1")	240 (minimum) (9.44")
	X Large	105 ± 3mm (4.13" ± 0.1")	240 (minimum) (9.44")
	XX Large	113 ± 3mm (4.44" ± 0.1")	240 (minimum) (9.44")
<b>Thickness</b> Millimetres (Inches)	<b>Palm</b>	<b>Finger</b>	
	1.25mm (0.0492")	1.45mm (0.0571")	

### Packaging Configuration & Labelling:

Packing: 120 pairs per case  
(12 pairs per inner bag)

Labelling: The inner tags and outer cartons have the following information: product description, brand, size and net quantity of gloves, country of origin, name and address of distributor and EN388 mechanical protection symbol.

Barcodes: GS1 format.

### Hangtag



### EN388 - Mechanical Risks

Pictogram	Abrasion	Cut	Tear	Puncture
<p>EN388 4 5 4 4</p>	<p>4</p> <p><i>This 1-4 digit represents how many cycles of a coarse surface the glove can handle until failure.</i></p> <p>1 = 100 2 = 500 3 = 2000 4 = 8000</p>	<p>5</p> <p>1 = 1,2 factor. 2 = 2,5 factor. 3 = 5 factor. 4 = 10 factor. 5 = 20 factor.</p>	<p>4</p> <p><i>The higher this 1-4 digit the more torque (Nm) a glove can take in a tearing motion.</i></p> <p>1 = 10 Nm 2 = 25 Nm 3 = 50 Nm 4 = 75 Nm</p>	<p>4</p> <p><i>1 = 20 Nm until break. 2 = 60 Nm until break. 3 = 100 Nm until break. 4 = 150 Nm until break.</i></p>

For more information:  
customer.service@theglovecompany.com